BIBLIOGRAPHY

1. Arora, N. and Kumar D. (2000): "System analysis and maintenance management for the coal Gandling system in a paper plant", IJOMAS , 16(2), 156-173.
2. Arulmozhi, G. (2002): "Reliability of an M-out-of-N warm standby system with R repair facilities", OPSEARCH, 39(2), 77-87.
3. Asha, G., P.G. Shankarn and Nair N.U. (2003): "Probability mode is with constant total failure rate", communications in Statistics, 321 (6), 1089-1099.
4. Balagurusamy, E. (1984): "Reliability Engineering, Tata Megraw Hill Publishing Company Limited", New Delhi.
5. Barlow, R.D. and Proschan, F. (1965): "Mathematical Theory of Reliability" JohnWilsey, New York.
6. Bhardwaj, P. (2003): "Reliability modeling of some technological systems", Ph.D. thesis, C. C. S. University. Meerut.
7. Epstein, B. and Sobel, M. (1954): "Life testing", *J. Amer. Statist. Assoc.*, 48, 486-502.
8. Goel, L.R., Sharma, G.C. and Gupta, R. (1985): "Cost analysis of a two-unit cold standby system under different weather conditions",*Microelectron. Reliab.*, 25, 655-659.

9. Goel, L.R., Sharma G.C. and Gupta P. (1985): "Stochastic behaviour and profit function of a system with precautionary measures under abnormal weather", *Microelectron. Reliab.*,Vol. 25, 661-664.

10. Goel, L.R., Sharma, G.C. and Gupta, R. (1986): "Reliability analysis of a system with preventive maintenance and two types of repair",*Microelectron. Reliab.*, Vol. 26, 429-433.

11. Goel, L.R. and Srivastava P. (1991): "Profit analysis of two-unit redundant system with provision of rest and correlated failures and repairs". *MicroelectronReliab.*, Vol. 31, 827-833.

12. Goel, L.R. and Srivastava P. (1996): "A warm standby redundant system with correlated failures and repairs". *MicroelectronReliab.*, Vol. 36, No.6, 793-797.

13. Gopalan, M.N. (1975), "Availability and reliability of one-server two-unit system with imperfect switch over", *IEEE Trans. Reliab.*, R-24, 218.

14. Goyal, V. and Murari, K. (1984): "Cost analysis of a two-unit standby system with two types of repairman",*Microelectron Reliability*, *24, 849-855.*

15. Goyal, A. Taneja, G. and Singh, D.V. (2009): "Analysis of a two unit cold standby system working in a sugar mill with operating and rest period", *Caledonian Journal of Engineering, Oman, 5(1), 1-5.*

16. Goyal, A. Taneja, G. and Singh, D.V. (2010): "Reliability modeling and analysis of a sulphated juice pump system comprising three identical units with two types of working capacity and rest period", *Pure and Applied Mathematical Sciences*, *71(1-2), 133-143.*

17. Gupta, R. and Goel, L.R. (1989): "Profit analysis of two-unit priority standby system with administrative delay in repair", *Int. J. Systems Sci.* Vol. 20, 1703-1712.

18. Gupta, R. and S. Bansal (1991): "Cost analysis of a three-unit standby system subject to random shocks and linearly increasing failures rates." *Reliability Engineering and System Safety*, Vol. 33, 249-253.

19. Gupta, R and A. Chaudhary (1995): "Stochastic analysis of a priority unit standby system with repair machine failure", *Int. Jr. Systems Science* Vol. 26, 2435-2440.

20. Gupta, R., Kishan, R. and Goel, R. (1997): "Analysis of a system having super priority, priority and ordinary units with arbitrary distributions", *Microelectron. Reliab.*, 37, 851-856.

21. Gupta, Krishan R.R and Kumar P. (1999): "A two non-identical unit parallel system with correlated life times", *Int Jr. Systems Science*, Vol. 30(6), 1123-1129.

22. Gupta, R. and Shivakar (2003): "A two non-indentical unit parallel system with waiting time distribution of repairman", IJOMAS, Vol. 19(1), 77-90.

23. HoylandArnlijot and Marvin Rausand (1993): "System Reliability Theory Models and Statisitcal Methods, John Wiley of Sons", INC.

24. Khurana, V. (2005): "Applied reliability models in technological systems", U.P. Technical University, Lucknow.

25. Kumar, R., Vashishtha, U. and Tuteja, R.K. (2001): "A two unit redundant system with degradation and replacement", Pure and Applied Mathematics Sciences, LIV, 27-38.

26. Kumar, R., Mor, S.S. and Sharma, M.K. (2010): "Reliability and cost-benefit analysis of a three stage operational warranted sophisticated system with various minor and major faults", *Pure and Applied Mathematika Sciences*, *72, 29-38.*

27. Mine, H. and Kaiwal, H. (1979): "Repair priority effect on availability of two-unit system", *IEEE Trans. Reliab.*, 28, 325-326.

28. Mogha, A.K. and A.K. Gupta (2002), "A two priority unit warm standby system model with preparation for repair." Aligarh Journal of Stratistics, Vol. (22), 73-90.

29. Murari, K. and Goyal, V. (1983): "Reliability system with two types of repair facilities", *Microelectron. Reliab.*, 23, 1015-1025.

30. Nanda Jyoti, (2003): "Profit evaluation of some reliability models for sophisticated systems with resume and repeat repair policies", Ph.D. Thesis, M.D. University, Rohtak.

31. Nakagawa, T. and Osaki, S. (1974): "Optimum preventive maintenance policies maximizing the mean time to the first system failure for a two-unit standby redundant system", *J. Optimization Theory*, April 14, 115-129.

32. Nakagawa, T. (1976): "On a replacement problem of a cumulative damage model", J. Oper. Res. Quart., 27, 895-900.

33. Sinha, S.M. and D.V.S. Kapil (1979), "Two unit redundant system with slow-switch." IEEE Trans. Reliab., R-28, 418.

34. Singh, S.K. and S.P Singh (2002), "The configurational modeling and analysis of wire rod nil system." Aligarh Journal of Statistics, Vol. 22, 43-62.

35. Taneja, G. (2005): "Reliability and profit analysis of a system with PLC used as hot standby", Proceeding of International Conference on Reliability and safety engineering organized by IIT, Kharagpur at its extension centre at Bhbneshwar (Orissa).

36. Taneja, G., and Nanda, J. (2003):"Probabilistic analysis of a two-unit cold standby system with resume and repeat repair policies", Pure and Applied Mathematika Sciences, Vol. LVII, Nol. 1, 2, 37-49.

37. Taneja, G. and Naveen V. (2003): "Comparative study of two reliability models with patience time and chances of non-availability of expert repairman", Pure and Applied Mathematika Sciences, Vol. LVII (1-2), 23-35.

38. Taneja, G. Tyagi, V.K. and Bhardwaj, P. (2004): "Profit analysis of a single unit programmable logic controller (PLC)", Pure and Applied Mathematika Sciences. Vol. LX (1-2), 55-71.

39. Taneja, G., Khurana, V. and Rizwan, SM. (2006): "Economic analysis of a reliability model for two-programmes, logic controller cold standby system with four types of failure", *Pure and Applied Mathematics Sciences, LXIII, (1-2), 65-78.*

40. Taneja, G., Naveen, V. and Madan, D.K. (2001): "Reliability and profit analysis of a system with an ordinary and an expert repairman wherein the latter may not always be available", Pure and Applied Mathematika Science, LIV(1-2), 11-25.

41. Tuteja R.K. and Taneja G. (1991): "Proper utilization of a system with two identical repairmen", International Journal of Management and Systems, 7, 273-281.

42. Tuteja, R.K. and Taneja, G. (1993): "Profit analysis of a one-server one-unit system with partial failure and subject to random inspection", *Microelectron. Reliab*., 33, 319-322.

43. Tuteja, R.K. Arora, R.T. and Taneja, G. (1991): "Stochastic behavior of a two-unit system with two types of repairman and subject to random inspection", *Microelectron. Reliab.*, 31,79-83.

44. Tuteja, R.K. Arora, R.T. and Taneja, G. (1991): "Analysis of two-unit system with partial failures and three types of repair", Reliability Engineering and system Safety, 33,199-214.

45. Tuteja, R. K., Taneja, G. and Malik, A. (2001): "Reliability and profit analysis of two-unit cold standby system with partial failure and two type of repairman", *Journal of decision and mathematical sciences, 5-6(1-3), 45-58.*

46. Yadavalli, V.S.S. (2001). "Stochastic model of complex system consisting of generators each with main auxiliary switch boards", IJOMAS, Vol. 17(3), 231-242.